



**SAN JOAQUIN COUNTY
COMMUNITY DEVELOPMENT DEPARTMENT**

1810 E. HAZELTON AVE., STOCKTON, CA 95205-6232
PHONE: 209/468-3121 FAX: 209/468-3163

**Declaration and Certification of Lawful Installation of Finish Material:
Section 4.501 Environmental Quality Control
Section 4.504 Pollutant Control**

Material and Requirements

Adhesives, sealants and caulks	Must meet current VOC limit per section 4.504.2.1 of California Green Building Standards Code <i>Enter name of product(s) used and identify manufactures product specification and VOC limit:</i>		

Paints and coatings	Must meet current VOC limit per section 4.504.2.2 of California Green Building Standards Code <i>Enter name of product(s) used and identify manufactures product specification and VOC limit:</i>		

Aerosol paints and coatings	Must meet current VOC limit per section 4.504.2.3 of California Green Building Standards Code <i>Enter name of product(s) used and identify manufactures product specification and VOC limit:</i>		

Carpet Systems Section 4.504.3	All carpet installed in the building interior shall meet the testing and product requirements of one of the following: <ul style="list-style-type: none"> <input type="checkbox"/> Carpet and Rug Institute’s Green Label Plus Program <input type="checkbox"/> California Department of Public Health Standard Practice for the testing of VOCs (Specification 01350) <input type="checkbox"/> NSF/ANSI 140 at the Gold level <input type="checkbox"/> Scientific Certifications Systems Indoor Advantage™ Gold <i>Indicate the product and testing requirement used on the installed carpet(s) above A copy of verification shall be required</i>		
--	---	--	--

Carpet cushion Section 4.504.3.1	All carpet cushion installed in the building interior shall meet the requirements of the Carpet and Rug Institute Green Label program.		
<input type="checkbox"/> I certify that the Carpet pad /cushion meets the requirements of the Carpet and rug Institute label program			

Carpet Adhesive Section 4.504.4.3.2	All carpet adhesive shall meet the requirements of Table 4.504.1 of the California Green Building Standards Code <i>Enter name of product(s) used and identify manufactures product specification and VOC limit:</i>		

Resilient flooring systems Section 4.504.4	Where resilient flooring is installed, at least 50% of floor area receiving resilient flooring shall comply with the VOC emission limits defined in the Collaborative for High Performance Schools (CHPS) Low-emitting Materials List or certified under the Resilient Floor Covering Institute (RFCI) FloorScore program <input type="checkbox"/> <i>The installed flooring is certified under RFCI</i> <input type="checkbox"/> <i>The installed flooring meets the CHPS Low-emitting list</i>		
--	--	--	--

Composite wood products Section 4.504.5	Hardwood plywood, particleboard and medium density fiberboard composite wood products used on the interior or exterior of the building shall meet the requirements for formaldehyde as specified in ARB’s Air Toxics Control Measure for Composite Wood (17 CCR 93120 et seq.), by or before the dates specified in those sections in Table 4.504.5 <i>Enter name of product(s) used and identify product certification and specs</i> <i>Indicate the current maximum Formaldehyde emission limit for each product used</i>		

Declaration Statement:

I certify under penalty of perjury, under the laws of the State of California that the installed finish materials and components conform to all applicable codes and regulations. And the installation is consistent with the plans and specifications approved by the enforcing agency, and that the information provided is true and correct.

X _____ Date _____

Title (i.e.: Property Owner, Contactor, or Builder)